

Environmental Product Declaration

Drive^{IT} Low Voltage AC Drive
for ACS 400 frequency converter, 4 kW power



CERTIFIED ENVIRONMENTAL PRODUCT DECLARATION
S-P 00022
<http://www.environdec.com>



Organisational framework

ABB Oy, Drives in Finland forms part of ABB's Automation Technology Products division. The company develops, manufactures and markets electrical machines and drives for ABB Group customers world-wide and is responsible for several key product groups, including variable-speed AC drives and drive systems for speed control of electric motors.

Environmental management

The ISO 14001 international environmental management standard has been implemented and the Helsinki factory has been certified since 1996. Life cycle assessment (LCA) is applied continually to all product development.

Environmental performance

The data and calculations are in accordance with Product Specific Requirements (PSR) for Variable Speed Electric Drives, which specifies the following baselines for the LCA calculation.

Functional unit

The functional unit for the LCA is 1 kW of rated output power.

System boundaries

The life cycle assessment covers all environmental aspects for extraction and production of raw materials, manufacturing of main parts, assembly, transportation and use of the product, dismantling, fragmentation and disposal and recycling of scrap after end of life. It includes consumption of material and energy resources as well as emissions and waste generation.

Calculations are based on an estimated lifetime of 15 years when operating 5,000 hours per year. A Finnish mix of energy has been used for calculating energy consumption during manufacturing and an OECD mix of energy for calculating energy consumption during use and disposal.

Allocation unit

The factor for allocation of common environmental aspects during manufacturing (such as manufacturing waste) is calculated as used working hours in relation to the total annual production volume for the manufacturing at ABB Oy, Drives and mass for the manufacturing at the suppliers.

Product description

ABB Oy, Drives comprises the following product series

• ACS 100	power range	0.12 to 2.2 kW
• ACS 140	power range	0.12 to 2.2 kW
• ACS 160	power range	0.55 to 2.2 kW
• ACS 400	power range	2.2 to 37 kW
• ACS 600	power range	1.5 to 4,300 kW
• ACS 800	power range	1.1 to 500 kW

This document applies to the ACS 401 000 632 model which is a 400 V, 4 kW product with protection IP 21.

Material according to the table below is used for the product.

Type of material	kg / product	kg / kW
Steel	1.18	0.30
Copper	0.52	0.13
Aluminium	3.08	0.77
Plastics	0.78	0.19
Cardboard (package)	0.86	0.22
Other materials	0.34	0.09

Resource utilisation

	Manufacturing phase unit / kW	Usage phase unit / kW	Disposal phase unit / kW
Use of non-renewable resources			
Coal kg	4.55	1,266.13	-2.52
Aluminium (Al) kg	1.02	0.00	-1.00
Copper (Cu) kg	0.11	0.00	-0.07
Iron (Fe) kg	0.43	0.00	-0.30
Manganese (Mn) kg	0.00	0.00	0.00
Natural Gas kg	0.67	108.28	-0.28
Uranium (U) kg	0.00	0.03	-0.00
Oil kg	2.41	103.51	-1.49
Use of renewable resources			
Hydro Power MJ	0.29	3,202.37	0.00

Energy consumption and losses

Energy form	kWh / product			kWh / kW		
	Manufacturing phase	Usage phase	Disposal phase	Manufacturing phase	Usage phase	Disposal phase
Electrical energy	7.6	17,154.6	-	1.91	4,288.64	0.0
Heat energy	4.2	-	-	1.05	-	-

The Finnish electricity mix is defined as being 10 percent gas, 31 percent hydro, 40 percent nuclear, 2 percent oil and 17 percent stone coal. The average OECD electrical energy mix is defined as being 13 percent gas, 16 percent hydro, 23 percent nuclear, 7 percent oil, 33 percent stone coal, 6 percent lignite coal, 1.5 percent biomass & waste and 0.5 percent other. The resultant resource utilisation is shown in the table above.

Waste

	kg / kW
Hazardous waste	
During manufacturing	-
At disposal phase	-
Regular waste (to landfill)	
During manufacturing phase	0.02
At disposal phase	0.58

The classification data for emissions are as follows.

Environmental effect	Equivalent unit	Manufacturing phase	Usage phase
Global warming potential GWP	kg CO ₂ / kW	21.80	2,568.22
Acidification potential AP	kmol H ⁺ / kW	0.01	0.46
Eutrophication	kg O ₂ / kW	0.36	34.32
Ozone depletion potential ODP	kg CFC-11 / kW	0.00	0.00
Photochemical oxidants POCP	kg ethylene / kW	0.01	0.46

Additional qualifying factors

Recycling and disposal

The main parts of the product can be recycled - some parts need to be fragmented to separate different types of material. A list of parts and components that can be fragmented and recycled can be obtained from the manufacturer. See references.

Usage phase in relation to the total

It should be observed that the environmental impact during the usage phase is the most important. As an example, GWP for the usage phase is approximately 80 times larger than GWP for the manufacturing phase.

Category of impact	Usage as % of total
Global warming GWP	99.16 %
Acidification AP	98.72 %
Eutrophication	98.97 %
Ozone depletion ODP	-
Photochemical oxidants POCP	97.88 %

Third party certification

This EPD has been reviewed and found to comply with the Product-Specific Requirements for Variable speed electric drives PSR 2000:7, dated 2000-12-26 and with the Requirements for Environmental Product Declarations, EPD, MSR 1999:2, issued by The Swedish Environmental Management Council and dated 2000-03-27.

References

- LCA report, 3AFE 64429035
- PSR 2000:7 for Variable Speed Electric Drives, The Swedish Environmental Management Council
- User's Manual for type ACS 400 frequency converters from 2.2 to 37 kW, 3BFE 34020561 R0125
- ACS 400 frequency converter, Environmental Information, Recycling Instructions 3AFE 64428900
- MSR 1999:2 Requirements for Environmental Product Declarations, EPD, The Swedish Environmental Management Council

The above mentioned documents are available upon request from ABB Oy, Drives.

Time of validity

This Environmental Product Declaration which has been reviewed and approved by Det Norske Veritas Certification AB according to PSR 2000:7 and MSR 1999:2 is valid up to and including 31 March, 2004.

Accredited certification body

Det Norske Veritas Certification AB,
P.O. Box 30234, Warfvinges väg 19,
SE-104 25 Stockholm, Sweden.
Tel: +46 8 587 940 00 Fax: +46 8 651 70 43

GLOSSARY

Acidification, AP.

Acidification originates from the emissions of sulphur dioxide and oxides of nitrogen. In the atmosphere, these oxides react with water vapour and form acids which subsequently fall down to the earth in the form of rain or snow, or as dry depositions. Acidification potential translates the quantity of emission of substances into a common measure to compare their contributions to the capacity to release hydrogen ions.

Eutrophication.

Nutrients (mainly nitrogen and phosphorus) from sewage outfalls and fertilised farmland accelerate the growth of algae and other vegetation in water. The degradation of organic material consumes oxygen resulting in oxygen deficiency and fish kill. Eutrophication translates the quantity of emission of substances into a common measure expressed as the oxygen required for the degradation of dead biomass.

Global warming potential, GWP.

Some of the gases in the earth's atmosphere (in particular water vapour and carbon dioxide) have an ability to absorb infrared radiation. They do not prevent sunlight reaching the earth's surface, but they do trap some of the infrared radiation emitted back into space causing an increase in the surface temperature. Global Warming Potential, GWP100, translates the quantity of emission of gases into a common measure to compare their contributions - relative to carbon dioxide - to the absorption of infrared radiation in 100 years perspective.

Life cycle assessment, LCA.

A management tool for appraising and quantifying the total environmental impact of products or activities over their lifetime by analyzing the entire life cycle of particular materials, processes, products, technologies, services or activities. Life cycle assessment comprises three complementary components - inventory analysis, impact analysis and improvement analysis.

Ozone depletion potential, ODP.

Ozone forms a layer in the stratosphere protecting plants and animals from much of the sun's harmful UV-radiation. The ozone levels have declined as a consequence of CFCs and halons released into the atmosphere. A depletion of the ozone layer will increase the UV-radiation at ground level. Ozone depletion potential translates the quantity of emission of gases into a common measure to compare their contributions - relative to CFC-11 (a freon) - to the breakdown of the ozone layer.

Photochemical ozone creation, POCP.

Photochemical ozone or ground level ozone is formed by the reaction of volatile organic compounds and nitrogen oxides in the presence of heat and sunlight. Ground-level ozone forms readily in the atmosphere, usually during hot summer weather. Photochemical ozone creation potential translates the quantity of emission of gases into a common measure to compare their contributions - relative to ethylene - to the formation of photochemical oxidants.



ABB Oy

Drives
P. O. Box 184
FIN - 00381 Helsinki
Finland
Telephone +358 10 22 11
Telefax +358 10 222 2681
www.abb.com/motors&drives



441 025
Printed matter

HANSAPRINT/xxxx/2001

Ad agency PIRTEK#10539

3AFE 64292684 REV B EN 17.6.2002 Specifications subject to change without notice.
The Industrial[®] wordmark and all above-mentioned product names in the form Drive[®] are registered or pending trademarks of ABB.